



720p HD
Video Quality



Sound & Motion
Detection Alerts



microSDXC
Card Slot



16 Feet
Night Vision



Wi-Fi
Signal Locator



mydlink® Apps for
Remote Viewing



DCS-936L HD WI-FI CAMERA

Features

Premium Resolution and Visibility

- 120° Field of View for wider camera coverage¹
- HD 720p resolution image quality
- 1 Megapixel progressive CMOS sensor
- See up to 16 feet in complete darkness with built-in IR LEDs
- Supports H.264/MJPEG video codecs
- 4x digital zoom for close-up viewing

Security

- Sound and motion detection with e-mail/push alert notifications
- microSDXC card slot for local recording continuously, based on event triggers or according to a schedule²
- Built-in microphone

Ease of Use

- WPS support for easy wireless connection
- Wi-Fi signal locator LED guides you to the best placement for your camera
- Mobile app enabled setup

Convenient Control with mydlink Support

- mydlink app support for iPhone, iPad, Android devices and Windows phones⁴
- mydlink.com web portal for easy viewing and management

Overview


The HD Wi-Fi Camera (DCS-936L) provides crisp HD 720p video, making it easy and convenient to watch over your home no matter where you are. Place it anywhere and stay informed with automatic push alert notifications whenever sound or motion is detected. The DCS-936L is a standalone surveillance camera that requires no special hardware or software, and can run independently even without a PC. 16 feet of night vision allows you to see in total darkness and with the microSDXC card slot you can record video footage up to 128 GB directly from the camera so you never miss a moment. Stream live HD 720p video to your smartphone or tablet with the mydlink app for remote monitoring.

Easy to Setup, Even Easier to Use

The HD Wi-Fi Camera features a Wi-Fi signal locator LED which helps you determine optimum Wi-Fi connection when deciding where to place your camera. Once set up, the DCS-936L delivers the confidence of HD 720p video clarity, ensuring rich detail and crisp image quality for your surveillance streaming and recording. Record footage directly to a microSDXC card up to 128 GB for hassle-free recording and playback³ or simply add a mydlink Camera Recorder (DNR-202L) to locally record up to 4 D-Link Wi-Fi Cameras for a scalable alternative for recording and storing video.

Convenient Access Anytime, Anywhere with mydlink®

Access your camera through the free mydlink mobile app or website to view and manage your camera through your tablet, mobile phone, laptop or desktop, no matter where you are⁴.



Technical Specifications

Camera

Hardware Profile	<ul style="list-style-type: none"> 1/4" 1 megapixel progressive CMOS sensor 16 feet IR illumination distance Minimum illumination: 0 lux with IR LEDs on Built-in Infrared-Cut Removable (ICR) Filter module 4x digital zoom Focal length: 2.45 mm 	<ul style="list-style-type: none"> Aperture: F2.4 Angle of view: <ul style="list-style-type: none"> (H) 100° (V) 54° (D) 120° Built-in microphone
Image Features	<ul style="list-style-type: none"> Adjustable image size, quality, frame rate and bit rate Adjustable brightness, saturation, contrast, sharpness and hue 	<ul style="list-style-type: none"> Time stamp and text overlays Flip & mirror
Video Compression	<ul style="list-style-type: none"> Simultaneous H.264/MJPEG format compression 	<ul style="list-style-type: none"> JPEG for still images
Video Resolution (at up to 30 fps)	<ul style="list-style-type: none"> 1280 x 720 640 x 352 	<ul style="list-style-type: none"> 320 x 176
Audio	<ul style="list-style-type: none"> PCM 	<ul style="list-style-type: none"> ADPCM
External Device Interface	<ul style="list-style-type: none"> Power LED WPS Button microUSB Power Connector 	<ul style="list-style-type: none"> Reset Button microSD Card Slot LED Wi-Fi Signal Locator

Network

Network Protocols	<ul style="list-style-type: none"> IPv4, IPv6, ARP, TCP, UDP, ICMP DHCP Client NTP Client (D-Link) DNS Client DDNS Client (D-Link) SMTP Client 	<ul style="list-style-type: none"> HTTP Server PPPoE UPnP, UPnP Port Forwarding RTP, RTSP HTTPS (for configuration) Bonjour
Security	<ul style="list-style-type: none"> Administrator and user group protection Password authentication 	<ul style="list-style-type: none"> HTTP and RTSP digest encryption
Wireless Connectivity	<ul style="list-style-type: none"> 802.11n/g wireless with WPA/WPA2 encryption 	<ul style="list-style-type: none"> Operates on 2.4GHz frequency band

Recording

microSD Card Slot	<ul style="list-style-type: none"> Supports microSD/SDXC 	<ul style="list-style-type: none"> Up to 128 GB
mydlink Camera Recorder (DNR-202L)	<ul style="list-style-type: none"> Supports 2 external USB hard drives up to 4 TB each Records up to 4 D-Link Wi-Fi Cameras 	<ul style="list-style-type: none"> DNR-202L and USB hard drives sold separately

System Integration	
System Requirements for Web Interfaces	<ul style="list-style-type: none"> Operating system: Microsoft Windows 10⁵/8/7/Vista⁶ or Mac OS X (10.8 and above) Browser: Internet Explorer 8, Firefox 24, Chrome 45 or Safari 9.0.3 or higher
Event Management	<ul style="list-style-type: none"> Event notification and uploading of snapshots/video clips via e-mail (SMTP) Configurable motion detection windows Configurable sound level detection
Remote Access	
Remote Management	<ul style="list-style-type: none"> Configuration accessible via web browser
Mobile Support	<ul style="list-style-type: none"> mydlink Lite app for iOS, Android and Windows Phones <ul style="list-style-type: none"> Requires iOS 7 and above, Android 4.0 and above, or any version Windows Phone mydlink Plus app for iOS and Android devices <ul style="list-style-type: none"> Requires iOS 7 and above or Android 2.1 and above
General	
Power	<ul style="list-style-type: none"> Input: 100- 240VAC, 50/60 Hz Output: 5 V DC, 1.2 A
Power Consumption	<ul style="list-style-type: none"> 4.5 watts
Temperature	<ul style="list-style-type: none"> Operating: 32 to 104 °F (0 to 40 °C) Storage: -4 to 158 °F (-20 to 70 °C)
Humidity	<ul style="list-style-type: none"> Operating: 20% to 85% non-condensing Storage: 20% to 85% non-condensing
Certifications	<ul style="list-style-type: none"> CE CE LVD FCC Class B ICES C-Tick
Dimensions	<ul style="list-style-type: none"> 1.89 x 2.56 x 3.17 inches (W x D x H)
Package Contents	<ul style="list-style-type: none"> HD Wi-Fi Camera (DCS-936L) microUSB power adapter Mounting screws Quick install guide
Warranty	<ul style="list-style-type: none"> 1 Year Limited For warranty and regulatory information please visit http://support.dlink.com/warranty
Order Information	
Part Number	Description
DCS-936L	HD Wi-Fi Camera

¹ Field of view based on diagonal (D) measurements

² A microSDXC Class 6 card or above is recommended (not included). Supports card capacities up to 128GB.

³ Use of audio or video equipment for recording the image or audio of a person without their knowledge and consent is prohibited in certain states or jurisdictions. The end-user assumes all liability for compliance with applicable state, local and federal laws.

⁴ The DCS-936L is not supported by the mydlink Home app and is not compatible with D-Link's Connected Home Series.

⁵ Windows Edge not currently supported.

⁶ Computer must adhere to Microsoft's recommended system requirements.

For more information

U.S.A. | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com

©2017 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link, the D-Link logo and mydlink logo are trademarks or registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Other trademarks or registered trademarks are the property of their respective owners. iPhone and iPad are registered trademarks of Apple Inc. Android is a trademark of Google Inc. Windows is a registered trademark of Microsoft Inc.



mydlink Lite only